

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
11 December 2003 (11.12.2003)


PCT

(10) International Publication Number  
**WO 03/102524 A1**

- (51) International Patent Classification<sup>7</sup>: **G01L 3/10**, 5/00, G01M 13/04
- (21) International Application Number: PCT/US03/16850
- (22) International Filing Date: 29 May 2003 (29.05.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
60/383,945 29 May 2002 (29.05.2002) US
- (71) Applicant (for all designated States except US): **THE TIMKEN COMPANY** [US/US]; P.O. Box 6930, Canton, OH 44706-0930 (US).
- (72) Inventor; and  
(75) Inventor/Applicant (for US only): **VARONIS, Orestes, J.** [US/US]; 1340 Irondale Circle NE, North Canton, OH 44720 (US).
- (74) Agent: **NOLTE, Nelson, D.**; Polster, Lieder, Woodruff & Lucchesi, L.C., 763 South New Ballas Road, St. Louis, MO 63141 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report

[Continued on next page]

(54) Title: IN-BEARING TORQUE SENSOR ASSEMBLY



(57) **Abstract:** The present disclosure provides a device for sensing a torque applied through a shaft (18). The device includes a shaft (18) and a bearing (40) attached to the shaft (18). The bearing (40) includes an inner race (44), an outer race (42) and a plurality of rolling elements (46). A magnetoelastic ring (24) is press-fit onto the inner race (44). An eddy current or a magnetic field sensor (30) is placed in close proximity to the magnetoelastic ring (24). In the case of an eddy current sensor (30), the magnetoelastic ring (24) is not magnetized. In the case of a magnetic field sensor (30), the magnetoelastic ring (24) is magnetically circularly polarized. In either case, the chosen sensor (30) senses the induced changes of the magnetoelastic ring (24) characteristics and its associated electronics provides a measure of the applied torque.